

# SeaRox® SL 620(128)<sup>NA</sup>

SeaRox SL 620(128)<sup>NA</sup> is a rigid slab made of stone wool.

## Application

SeaRox SL 620(128)<sup>NA</sup> is primarily used as part of A-class constructions for bulkhead and deck.

Certified according to IMO 2010 FTP Code by DNV-GL and USCG.



## Product properties

Properties	Performance		Norm
Thermal conductivity	T (°C) λ (W/mK)	10 0,035	EN 12667
Nominal density	128 kg/m <sup>3</sup>		EN 1602 / IMO
Compressive strength	-		EN 826
Fire classification	Non-combustible Approved for A constructions		IMO 2010 FTP Code
Water absorption (short term)	< 1 kg/m <sup>2</sup>		EN 1609 AC
Max. Application Temperature	Wool: 750°C		-
Sound absorption directly mounted	-		ISO 354 (approximated) Evaluated after ISO 11 654
Facings	-		IMO 2010 FTP Code


## Dimensions

SeaRox SL 620(128)<sup>NA</sup>

Thickness (inch): 1", 1,57", 2", 2.36", 3", 4"

Length (inch): 48"

Width (inch): 24", 36"



0575

As ROCKWOOL has no control over insulation design and workmanship, accessory materials or applications conditions, ROCKWOOL does not warranty the performance or result of any installation containing ROCKWOOL products. ROCKWOOL's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose. ROCKWOOL Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.

ROCKWOOL® Technical Insulation, ROCKWOOL®, SeaRox® and ProRox® are registered trademarks of ROCKWOOL International A/S and cannot be used without a prior written consent.

Type approvals	USCG/DNV-GL approval
A60 class steel bulkhead	164.105/EC0575/MEDB00002HN
A60 class steel deck	164.105/EC0575/MEDB00002HT
Non-combustibility	164.109/EC0575/MEDB0000128 rev. 4

For more Type approvals please refer to our MED/USCG certificates on [rti.rockwool.com](http://rti.rockwool.com)